




版本 Rev	日期 Date	变更文件号 ECN NO.	变更内容 Revisions	设计 By
V1.0	18.10.19		新增图	王桂林

Motor Connctions:



Brake Connections



Common Rating

Step angle	1.8°
Position accuracy	1.8±0.09°
Dielectric strength	500V/AC 1min
Insulation resistance	100MΩhm(500VDC)
Insulation class	B
Temp rise(Max)	80K
Radial play	Max:0.02mm(Load 4.50g)
Axial play	Max:0.08mm(Load 900g)

Specification:

Current/phase	5.0 A
Voltage	3.3 V
DC Resistance/phase ±10%	0.43Ω
Inductance/phase ±20%	2.0 mH
Holding torque	3.0 N·M
Inertia	0.69 kg·cm ²
Weight	1.3 kg

设计 Designed	王湾松	日期 Date	2021.04.21	材料 Material	第一角画法 First Angle projection	深圳市雷赛智能控制股份有限公司 SHENZHEN LEADSHINE TECHNOLOGY CO., LTD.
审核 Checked	黄捷建	2021.04.21		版本/版次 Scale	比例 Scale	混合式步进电机
批准 Approved	黄捷建	2021.04.21		A/01		60CM30X-BZ
料号 Part No.	LS-MT-01-07A	共 1 套 1 of 1	第 1 套 Sheet 1 of 1	图号 DWG. NO.	LS-60CM30X-BZ	